



9.0L WATER BASED POLYMER SOLAR PANEL BLOCK-OUT STORED PRESSURE CANISTER



SPECIFICATIONS

PART NUMBER	GPVSTOP9
AGENT CAPACITY	9.0 LITRES
AGENT TYPE	WATER BASED POLYMER
TOTAL MASS	12.4KG
PRESSURE	1000KPA
NOZZLE SIZE	3.2MM
DISCHARGE TIME	48 SECONDS
EFFECTIVE RANGE	10 METRES
DIMENSIONS	W181 X H630MM
CYLINDER PRESSURE TEST	5 YEARLY
PERIODIC TEST PRESSURE	2.5MPA
CYLINDER CONSTRUCTION	STAINLESS STEEL
VALVE STEM	BRASS
CYLINDER FINISH	STAINLESS STEEL
HANDLE FINISH	STAINLESS STEEL
VALVE FINISH	NICKEL PLATED BRASS



PVSTOP
2-(2-BUTOXYETHOXY)ETHANOL 1-10%, NITROGEN <=89%
**SOLAR PANEL
BLOCK OUT**
9.0L WATER BASED POLYMER
DANGEROUS GOODS CLASS: 2.2
COMPRESSED GAS, N.O.S. (CONTAINS NITROGEN)
UN NUMBER: 1956
HAZCHEM CODE: 2TE
ADDITIONAL INFORMATION IS LISTED IN THE SAFETY DATA SHEET.
STORED PRESSURE
PVSTOP INTERNATIONAL PTY LTD
6 / 276-278 NEW LINE ROAD, DURAL NSW 2158. AUSTRALIA
PHONE: +61 (0) 2 9652 5000
EMERGENCY: +44 (0) 1536 408409 (9-5PM)
WWW.PVSTOP.COM.AU